



DCN-CON Concentus Basic



The DCN-CON is the standard delegate conference unit that enables delegates to speak, register a request-to-speak, register a response request, listen to the speaker and vote. It has low susceptibility to interference from mobile phones. A socket is provided to connect the pluggable microphones (DCN-MICS and DCN-MICL, to be ordered separately). The flat-panel loudspeaker offers superior acoustics with minimal feedback, thus increasing intelligibility. It is automatically muted when the microphone is activated. When the unit is not being used, the loudspeaker panel conveniently folds down. There are five voting buttons for all kind of voting. An external contact is available to connect external fingerprint readers.

Functions

Controls and indicators

- Built-in, fold-away, flat-panel loudspeaker, automatically muted if the microphone is on
- Microphone 'on/off' or 'request-to-speak' button
- 'Microphone on' indicator at the top of the loudspeaker
- Tri-color indicator above the microphone button:
 - Red 'Microphone on' indicator
 - Green 'Request-to-speak' confirmation indicator
 - Yellow 'VIP' indicator. 'VIP' LED is lit when the delegate unit is part of the notebook, which is only available when PC control software is used
- Five voting buttons with yellow LED confirmation indicators These can be used to register:

- ▶ **Low susceptibility to mobile phones**
- ▶ **Compact, attractive delegate unit**
- ▶ **Built-in fold-away flat-panel loudspeaker**
- ▶ **Five voting buttons**
- ▶ **Cable connections located underneath the unit**
- ▶ **External present and fraud contact**

- PRESENT, YES (+), NO (-), ABSTAIN (X), (parliamentary voting)
- Numerals: 1 to 5 (multiple choice or opinion polls)
- Rating scale: - -, -, 0, +, ++ (audience response)

Connections

- Socket for pluggable microphone
- 2 m (78.7 in) cable terminated in a molded six-pole circular connector
- Six-pole circular connector for loop-through connections
- Eight-pole modular jack connector for Intercom Handset LBB 355/00 and external present and Fraud contact e.g. a fingerprint reader

Certifications and Approvals

Region	Certification
Europe	CE

Technical Specifications

Electrical

Frequency response	30 Hz to 20 kHz
Headphone load impedance	> 32 ohm
Output power	2 x 15 mW/32 ohm

Mechanical

Mounting	Tabletop (portable or fixed mounting) and flush mounting
Dimensions (H x W x D)	(without microphone)
Tabletop	50 x 275 x 155 mm (2.0 x 10.8 x 6.1 in)
Flush mounted	30 x 275 x 155 mm (1.2 x 10.8 x 6.1 in)
Weight	1.4 kg (3.1 lb)
Color top	Charcoal (PH 10736) with silver (RAL 9022) panel
Color base	Charcoal (PH 10736)

Ordering Information**DCN-CON Concentus Basic**

pluggable microphone, voting, microphone to be ordered separately

Accessories**DCN-MICS Pluggable Short Microphone**

length 310 mm (12.2 inch)

DCN-MICL Pluggable Long Microphone

length 480 mm (18.9 inch)

Europe, Middle East, Africa:
 Bosch Security Systems B.V.
 P.O. Box 80002
 5600 JB Eindhoven, The Netherlands
 Phone: + 31 40 2577 284
 Fax: +31 40 2577 330
 emea.securitysystems@bosch.com
 www.boschsecurity.com

Americas:
 Bosch Security Systems, Inc.
 130 Perinton Parkway
 Fairport, New York, 14450, USA
 Phone: +1 800 289 0096
 Fax: +1 585 223 9180
 security.sales@us.bosch.com
 www.boschsecurity.us

Asia-Pacific:
 Bosch Security Systems Pte Ltd
 38C Jalan Pemimpin
 Singapore 577180
 Phone: +65 6319 3450
 Fax: +65 6319 3499
 apr.securitysystems@bosch.com
 www.boschsecurity.com

Represented by