



Morrison's
PUBLIC ADDRESS & PROFESSIONAL AUDIO

www.morrisonsav.com.au
sales@morrisonsav.com.au
Phone: 08 9493 1196
Fax: 08 9459 2869
Mob: 0407442822

Wireless Portable Amplifiers



VICTORY2000

Modulized Wireless Portable Sound System

General Features

- All in 1. Easy to operate in indoor & outdoor applications.
- All in 1. Easy to operate in indoor & outdoor applications.
- New stylish design rugged aluminum enclosure.
- An anti-scratch bumper on the front downside edge is designed to avoid any scratches or marks during transportation.
- 100 - 240 V AC switch mode power supply.
- Two-way speaker system with crossover.
- 24V DC supply by 2 built-in rechargeable lead-acid batteries.
- Slots for two UHF PLL true diversity/diversity type receivers.
- 2 XLR/Phone combo connectors as wired mic input.
- Inputs : MIC IN x 2 \ LINE IN \ AUDIO LINK IN.
- Outputs : LINE OUT \ AUDIO LINK OUT \ SPKR OUT.
- Controls : MIC IN Vol, Tape, Line Vol, Bass, Treble, Master Vol Line in & out RCA jack.
- MIC IN mode selector for Speech / Music.
- Voice Priority circuitry.
- Integrated preamplifier, mixer and amplifier circuitry.
- Unique design of audio link Master/Slave circuitry enables the connection of 20 active speakers.
- Individual volume control for wired and wireless microphones.
- Integrated retractable 2-stage trolley and wheels.
- The CD player can be remotely operated from both front and rear unit.
- Versions :
 - CD/Digital player(USB) / (USB+pitch)
 - Digital recorder player
 - FM/AM tuner
 - Cassette recorder
- Charging indicator LED.
- Tripod mountable with ST-50(standard)/ ST-51(wind-up).

Specifications

Model	Victory 2000
Output Power	Max 200W 90W, (RMS)/4Ωload
Speaker System	2-way speaker & crossover
T.H.D.	< 0.5%
Audio Inputs	Mic in x 2 \ Line in \ Active in
Audio Outputs	Line out, Active out, SP(switched & unswitched)
Power Supply	90~260 V (150W) switch mode
Battery Type	12 V / 5 AH x2
Operating Life	3 hours in music >6 hours in speech
Charging Time	about 10 hours
Dimension (mm)	600H, 350W, 300D
Weight (kg)	25
Patent	Taiwan, China, USA, Europe, Australia
Approval	CE \ RoHS
Module type	receiver : SDR-6116m / 6216m / 6200m transmitter : RP-6016m / 6100m
Frequency Response	50Hz-20KHz±3dB
Antenna	Built-in