






E-mail......dnh@dnh.no


Web-Site..... www.dnh.no

<u>ENGLAND</u>	GERMA
DNH WW Ltd	DNH
Phone+ 44 1908 275 000	Phone
Fax+ 44 1908 275 100	Fax
E-maildnh@dnh.co.uk	E-mail.

GmbH ... + 49 040 6569 30-0 ... + 49 040 6569 30-30 .....dnh@dnh.de

DNH Speakers Inc Phone.....+ 1 484 494 5790 Fax.....+ 1 484 494 5793 E-mail..dnh@dnhspeakers.com







_	_	
Specifications		
Material / Color	ABS, Polypropylene / RAL 7035	
Mounting	Aluminum bracket	
Termination	Screw terminals in termination chamber	
Weight w/transformer	4,1 kg	
IP-rating	55	
Max. / min. amb. temp	90°C / -40°C	
Rated / max. power	50 W / 70 W	
SPL 1W/1m	104 dB	
SPL rated power	121 dB	
Effective freq. range	140 – 16000 Hz	
Dispersion (-6dB) 1kHz / 4kHz	65° / 20°	
Directivity factor, Q		
Options	Impedances, colors, labels	

## **Installation, Operation and Maintenance Procedures**

- Unscrew lid, lead cable through cable gland and connect to terminal according to required power or  $8\Omega$  red: black.
- Tighten cable gland and fasten termination chamber lid with a torque of 1-2 Nm to assure IP grade.
- Fasten the bracket to wall or ceiling with 3 screws.
- To change the position of the loudspeaker, please adjust the bracket (by loosening / tightening the screws) as required.
- For optimum performance, always use the correct voltage / power and operate within the frequency limits as
- Do not open loudspeaker when energized.
- This loudspeaker is supplied with a 2 year warranty against defective workmanship.

8Ω