

CS-154BS

WIDE RANGE SPEAKER

The CS-154BS is the voice alarm certification product. The CS-154BS Wide range speaker features an ABS resin enclosure and stainless steel bracket for all weather durability. It is comprised of a high-efficiency weather-resistant horn and a high quality sound cone speaker, providing clear and highly directional sound reproduction. The CS-154BS is equipped with a constant directivity horn (90° horizontal) to control sound directivity, realizing uniform and clear sound dispersion over a wide area.



Order no: CS-154BS

Specifications

Frequency response	150 Hz - 15 kHz
Connection	Ceramic screw terminals, thermal fuse, external connection box, 5-wire BS-compliant
Sensitivity (1#V, 1#n)	97 dB (330 Hz - 3.3 kHz, pink noise)
Directivity angle horizontal	140 °
Directivity angle vertical	200 °
Rated input (High Impedance)	15 W
Tappings	100 V : 670 Ω (15 W) / 1 kΩ (10 W) / 2 kΩ (5 W) 70 V : 330 Ω (15 W) / 670 Ω (7.5 W) / 1 kΩ (5 W) / 2 kΩ (2.5 W)
Dimensions (W x H x D)	366 x 230 x 310 mm
Dimensions (ø x D)	x 310 mm
Finish	ABS resin, paint, off-white (RAL 9010 or equivalent) Bracket: Stainless steel
Operating temperature	-20 °C to +55 °C (-4 °F to 131 °F)

CS-154BS

WIDE RANGE SPEAKER

Appearance

