

# CS-64BS

## WIDE RANGE SPEAKER

The CS-64BS is the voice alarm certification product. The CS-64BS Wide range speaker features an ABS resin enclosure and stainless steel bracket for all weather durability. It is comprised of a high-efficiency weather-resistant horn and a high quality sound cone speaker, providing clear and highly directional sound reproduction.



Order no: CS-64BS

### Specifications

Frequency response	130 Hz - 13 kHz
Connection	Ceramic screw terminals, thermal fuse, external connection box, 5-wire BS-compliant
Sensitivity (1#V, 1#m)	96 dB (1 W, 1 m at 330 Hz to 3.3 kHz pink noise) 93 dB (1 W, 1 m at 100 Hz to 10 kHz pink noise) 81 dB (1 W, 4 m at 100 Hz to 10 kHz pink noise)
Speaker component	12 cm cone-type (treated for splash proof)
Rated input (High Impedance)	6 W
Tappings	100 V : 1.7 k $\Omega$ (6 W) / 3.3 k $\Omega$ (3 W) / 10 k $\Omega$ (1 W) 70 V : 830 $\Omega$ (6 W) / 1.7 k $\Omega$ (3 W) / 3.3 k $\Omega$ (1.5 W) / 10 k $\Omega$ (0.5 W)
Dimensions (W x H x D)	233 x 224 x 249 mm
Dimensions ( $\phi$ x D)	x 249 mm
Finish	ABS resin, paint, papyrus white (RAL 9018 or equivalent) Bracket: Stainless steel
Operating temperature	-20 °C to +55 °C ( -4 °F to 131 °F)

# CS-64BS

WIDE RANGE SPEAKER

Appearance

